



MAVS-5

Vector Averaging 3 Axis Acoustic Current Meter With Long Term Deployment Capability

The **MAVS Current Meter** is a true 3 axis Acoustic Current Meter which employs a differential travel time measurement technique. The current meter takes measurements across 4 acoustic axes to provide a true vector averaged velocity measurement. Programmable burst mode and triggered sampling provide the most flexible current meter available.

The combination of small sensor geometry and differential travel time technique provide **unsurpassed resolution and accuracy**. The small transducer size significantly reduces the disturbance to water flow. While the standard range of measurement is 200 cm/sec, low speed measurement accuracy in the 0.03 cm/sec to 10 cm/sec range is preserved.


MAVS-5 includes **MAVSOF** Win95, Win98, WinNT user interface. Standard, commercially available software such as **Hyperterminal** or **Crosscut** may be used to communicate with the **MAVS-5** for getting real time data or for downloading and archiving recorded data to a PC. Software such as **MATLAB**, **Excel**, **Quattro Pro** and **Lotus 123** may be used for tabular display and graphing data.

OPTIONS:

- Titanium Housing
- Fast Temperature Sensor
- Conductivity sensor
- Pressure sensor
- Turbidity
- Compact Flash Logging Memory available, 1 GByte or more
- Moored Profiler (MMP) Config.



Faired Acoustic
Sensor



The **MAVS-5** employs a faired sensor head design with central strut and a 9.5 cm acoustic path length. The controller is a Persistor CF2 which is mounted by a connector beneath the main circuit board. A battery pack comprising 18 AA alkaline

cells provides all the necessary power to the instrument. A 4 pin connector mounted on the top end cap permits external power to be applied and provides TTL level, RS-232 or RS-485 communication capability.

Features:

- Unsurpassed Resolution and accuracy
- True 3 axis acoustic velocity measurement
- Field proven sensor technology
- No moving parts to foul
- Multi-mode operation, Vector averaging or event driven sampling
- Excellent vertical cosine response
- Differential travel time measuring technique
- Internal recording or direct reading
- Accuracy unaffected by instrument tilt or mooring motion
- Internal real time clock
- Digital communication via 5 Volt TTL, RS-232 or RS-485
- Temperature measurement
- 3-D Compass and Tilt Standard



NOBSKA

Innovation In Acoustic Current Measurements

Sales & Marketing NOBSKA
319 Seasons Drive
Punta Gorda, FL 33983
Tel: 941-766-0706 Fax: 941-766-0707
Email: dan-schaaf@att.net

Corporate Headquarters NOBSKA
P.O. Box 308, 12 Nobska Circle.
Woods Hole, MA 02543
Tel: 508-548-6450
Email: awilliams@nobska.net

Manufacturing NOBSKA
82 Technology Park Drive,
Falmouth, MA 02536
Tel: 508-292-2548
Email: pdugas@nobska.net

[HTTP://www.NOBSKA.net](http://www.NOBSKA.net)

SPECIFICATIONS:

<u>Parameter</u>	<u>Accuracy</u>	<u>Resolution</u>	<u>Range</u>
Speed	0.3 cm/sec	0.03 cm/sec	200 cm/sec (optional ranges available)
Direction	+/- 2 deg	1 deg	360 deg
Temperature	0.1 deg C	0.03 deg C	-5 to 45 deg C
Conductivity	0.2 mS/cm	0.02 mS/cm	0 to 75 mS/cm
Pressure	0.5% F.S. 0.04% optional 0.08% optional	0.024% F.S.	15, 30, 60, 450, 3,000, 7,500 & 10,000 PSI
Tilt	2 deg	0.1 deg	20 deg, 45 degree optional

Drift: NONE

Measurement Technique: Differential travel time, 3 axis

Acoustic Paths: 4 measured, 4 used

Power:

Internal Recording: 13.5 VDC, 18 AA Alkaline batteries, @ 4.8 Ah, optional lithium thionyl chloride 14.4 VDC @ 8.8 Ah

Direct Reading: External 12-15 VDC

Current Drain: 23 ma. Measuring
0.6 ma. Sleep Mode

Internal Recording Memory: 1 Gbyte compact Flash Card

Memory Usage: Dependent on sampling method and size of memory installed

Communications: TTL, RS-232 or RS-485 @ 38,400 baud maximum 115.2 K baud

Depth: 2,000 m. or 6,000 m.

Dimensions: Standard 2,000 m MAVS

Cylinder Diameter: 3.25 in.

Overall Length: 25 in.

Weight: Standard 2,000 m MAVS

Water: 2.6 lbs.

Air: 5 lbs.

Mooring Frame: 2000 lbs. Optional 10,000 lbs. available

Sampling Rates: 10 Hz in Earth Coordinates (resolved to V_e , V_n , V_{up}) or
15 Hz in instrument coordinates
25 Hz Raw Data, No Compass, No Options

Sea Cable: RS-485 or RS-232 4 wire (inquire for other communication protocols)

Data Record Size: Standard Instrument: 32 bytes per record for Day, Hour, Min, Sec, T, Tilt, V_e , V_n , V_u
Recorded as Binary and transmitted as ASCII Comma separated variables with CR LF

Operating Modes: Vector Averaging
Burst Mode (programmed for timed sampling)
Externally Triggered Sample
Continuous Sampling

Software: MAVSOFT Windows95, Windows98, Windows XP/NT user interface
Terminal Emulator: Hyperterminal, Crosscut or Tattleterm
Optional Graphical Software available upon request